



www.as-schwabe.de



STECKY

Combination units

Overview about all benefits :

STECKY

Ergonomic handle offers an excellent catch, even with gloves

Housing made of special plastic highly shock resistant

Powder-coated metal frame with edge protection

Cord made of heavy-duty rubber H07 RN-F from 3G2,5 up to 5G6

STECKY DUO

Velcro fastener for fixing the cord at the frame

Stable metal foot with cable rewind

STECKY DUO with phase display

STECKY DUO with 2 USB-Ports to recharge mobile phones, handlamp batteries and so on



STECKY

Combination unit

The STECKY range includes various combination units from 3,5 to 22 kW. Depending on the model, up to twelve outlets such as shock-proof sockets, USB-Ports or CEE sockets are available. All models of the STECKY range are intended for indoor, permanent outdoor and construction site use. Integrated protection devices avoid accidents.



Input / Plug	Output / Socket	Protection
16 A CEE CEE plug 230 V, 16 A, 3-pole	Shock-proof socket outlet German standard 230 V, 16 A, 2PE	FI/RCD RCD 40 A / 30 mA, 4-pole, A type RCBO 25 A / 30 mA, 2-pole, C curve, A type
16 A CEE CEE plug 400 V, 16 A, 5-pole	16 A CEE CEE socket 230 V, 16 A, 3-pole	
32 A CEE CEE plug 400 V, 32 A, 5-pole	16 A CEE CEE socket 400 V, 16 A, 5-pole	C16A MCB 16 A, 3-pole, C type MCB 16 A, 1-pole, C type
Phase display L1, L2, L3	32 A CEE CEE socket 400 V, 32 A, 5-pole	
	USB 2 USB-Ports 5 V / 2,1 A	



















STECKY

Combination units



Technical data

- Housing made of special plastic highly shock resistant
- Powder-coated metal frame with edge protection
- Ergonomic handle and cable rewind
- Dimensions: 230 x 417 x 220mm
- Tested according to DIN VDE 0620-1, ICE 60309, EN 61439-4, DIN EN 50525-2
- **IP44** splash proof
- Intended for indoor, permanent outdoor and construction site use

Model	Input	Output	Cord	Protection	Output power	PU	EAN	Art.-No.
 STECKY 11	Input 16 A  CEE plug 400 V, 16 A, 5-pole	Output 4x Shock-proof socket outlet 230 V, 16 A, 2PE 2x CEE sockets 400 V, 16 A, 5-pole 	2,5 m H07RN-F 5G2,5	–	≈ 11 kW	1	4011160609602	60960
 STECKY 11+	Input 16 A  CEE plug 400 V, 16 A, 5-pole	Output 4x Shock-proof socket outlet 230 V, 16 A, 2PE 2x CEE sockets 400 V, 16 A, 5-pole 	2,5 m H07RN-F 5G2,5	 FI/RCD 1x RCD 40 A / 30 mA, 4-pole, A type	≈ 11 kW	1	4011160609619	60961
 STECKY 12	Input 32 A  CEE plug 400 V, 32 A, 5-pole	Output 4x Shock-proof socket outlet 230 V, 16 A, 2PE 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 	4,5 m H07RN-F 5G4	 C16A 2 x MCB 16 A, 3-pole, C type 1 x MCB, 16 A, 1-pole, C type	≈ 22 kW	1	4011160609626	60962
 STECKY 13	Input 32 A  CEE plug 400 V, 32 A, 5-pole	Output 4x Shock-proof socket outlet 230 V, 16 A, 2PE 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 	4,5 m H07RN-F 5G4	 FI/RCD C16A 1x RCD 40 A / 30 mA, 4-pole, A type 1 x MCB, 16 A, 3-pole, C type 2 x MCB, 16 A, 1-pole, C type	≈ 22 kW	1	4011160609633	60963
 STECKY 14	Input 16 A  CEE plug 230 V, 16 A, 3-pole	Output 4x Shock-proof socket outlets 230 V, 16 A, 2PE 2x CEE sockets 230 V, 16 A, 3-pole 	2,5 m H07RN-F 3G2,5	–	≈ 3,5 kW	1	4011160608698	60869





















STECKY DUO

Combination units



Technical data

- Housing made of special plastic highly shock resistant
- Powder-coated metal frame with edge protection
- Ergonomic handle and cable rewind
- Dimensions: 400x450x252mm
- Tested according to DIN VDE 0620-1, ICE 60309, EN 61439-4, DIN EN 50525-2
- **IP44** splash proof
- Intended for indoor, permanent outdoor and construction site use

	Input	Output	Cord	Protection	Output power	PU	EAN	Art.-No.
 <p>STECKY DUO 1</p>	<p>Input 16 A</p>  <p>CEE plug 400 V, 16 A, 5-pole</p>	<p>Output</p> <p>8x Shock-proof socket outlet 230 V, 16 A, 2PE 4x CEE sockets 400 V, 16 A, 5-pole</p> 	<p>3,4 m H07RN-F 5G2,5</p>	 <p>1x RCD 40 A / 30 mA, 4-pole, A type</p>	<p>≈ 11 kW</p>	1	4011160609312	60931
 <p>STECKY DUO 2</p>	<p>Input 16 A</p>  <p>CEE plug 400 V, 16 A, 5-pole</p>	<p>Output</p> <p>8x Shock-proof socket outlet 230 V, 16 A, 2PE 2x CEE sockets 400 V, 16 A, 5-pole 2x USB ports 5 V / 2,1 A Phase display L1, L2, L3</p> 	<p>3,4 m H07RN-F 5G2,5</p>	 <p>1x RCD 40 A / 30 mA, 4-pole, A type</p>	<p>≈ 11 kW</p>	1	4011160609329	60932
 <p>STECKY DUO 3</p>	<p>Input 32 A</p>  <p>CEE plug 400 V, 32 A, 5-pole</p>	<p>Output</p> <p>6x Shock-proof socket outlets 230 V, 16 A, 2PE 2x CEE sockets 400 V, 16 A, 5-pole 2x CEE sockets 400 V, 32 A, 5-pole 2x USB ports 5V / 2,1A Phase display L1, L2, L3</p> 	<p>2,1 m H07RN-F 5G6</p>	 <p>1x RCD 40 A / 30 mA, 4-pole, A type 1 x MCB 16 A, 3-pole, C type 3 x MCB 16 A, 1-pole, C type</p>	<p>≈ 22 kW</p>	1	4011160609336	60933
 <p>STECKY DUO 4</p>	<p>Input 32 A</p>  <p>CEE plug 400 V, 32 A, 5-pole</p>	<p>Output</p> <p>6x Shock-proof socket outlets 230 V, 16 A, 2PE 1x CEE socket 230 V, 16 A, 3-pole 1x CEE socket 400 V, 16 A, 5-pole 2x CEE sockets 400 V, 32 A, 5-pole 2x USB ports 5 V / 2,1 A Phase display L1, L2, L3</p> 	<p>3,4 m H07RN-F 5G6</p>	 <p>1x RCD 40 A / 30 mA, 4-pole, A type 1 x MCB 16 A, 3-pole, C type 4 x MCB 16 A, 1-pole, C type</p>	<p>≈ 22 kW</p>	1	4011160609343	60934
 <p>STECKY DUO 5</p>	<p>Input 16 A</p>  <p>CEE plug 230 V, 16 A, 3-pole</p>	<p>Output</p> <p>7x Shock-proof socket outlet 230 V, 16 A, 2PE 4x CEE sockets 230 V, 16 A, 3-pole 2x USB ports 5 V / 2,1 A</p> 	<p>3,4 m H07RN-F 3G2,5</p>	 <p>1 x RCBO 25 A / 30 mA, 2-pole, C curve, A type</p>	<p>≈ 3,5 kW</p>	1	4011160609350	60935



STECKY

Combination units

The right model for every application:

- ✓ Combination units from 3,5 to 22 kW.
6 sockets up to 12 sockets available
- ✓ **Stable construction** for optimal use at construction sites, fairs, campsites ...
- ✓ **Weatherproof and isolated**
- ✓ **RCD / MCB protecting devices**
- ✓ **Comfortable handling by a huge handle**
- ✓ **USB-port** to recharge mobile phones, handlamp batteries and so on



Your partner for professional lighting and electrical products

as - Schwabe GmbH

Merkurstraße 10
D - 72184 Eutingen

Tel. +49 7457 9 48 53 10
Fax +49 7457 9 48 53 30

d.mueck@as-schwabe.de
www.as-schwabe.de

as[®]
Schwabe
TechnikProdukte